First Observation of Accelerator Origin Neutrino Beam After Passing Through 250km of Earth

Takasumi Maruyama

30 November, 2000

abstract

We are performing the KEK-Kamioka long base-line neutrino experiment (K2K) to search for the neutrino oscillation suggested by the Kamiokande results. In order to carry out this experiment successfully, we prepared a pion monitor and a muon monitor as secondary beam monitors. The pion monitor measured kinematics of produced pions just after a production target to estimate neutrino beam properties and the muon monitor behind a beam-dump after a decay volume measured a muon profile to steer the neutrino beam.

The pion monitor successfully measured the pion kinematics. From this data, we can predict the energy spectrum of the neutrino beam at the near detector and Super-Kamiokande(SK). Regarding the ratio of neutrino event rate at the near detector and SK, we achieved the accuracy within $^{+9.1\%}_{-10.1\%}$ for the June run and $^{+5.4\%}_{-8.7\%}$ for the November run, in 1999.

The neutrino beam-line was successfully directed toward SK employing the Global Positioning System(GPS). We steered the neutrino beam direction to SK within 1 mrad with the muon monitor. The muon range detector as near detector measured the neutrino events. The neutrino beam direction to SK was confirmed by the muon range detector to be within 1 mrad. Measured properties of the neutrino beam: the profile of the neutrino beam and the energy spectrum and the angle of generated muons by charged current neutrino interactions, are consistent with the Monte Carlo(MC) expectation.

GPS system successfully synchronized the timing between KEK and SK. With utilizing this timing synchronization, $\sim 5.0\times10^{-6}$ reduction of background events is achieved, resulting 1.6×10^{-3} background events from atmospheric neutrinos.

In June and November, 1999, we injected a total of 7.5×10^{18} protons on the target of which 6.6×10^{18} is used for the analysis. Three fully contained neutrino events were observed in the fiducial volume of SK. Expected number of neutrino events at SK is calculated by use of the pion monitor and the near detector data to be $11.34^{+1.70}_{-1.83}$. The probability that we observed 3 events or less against this expectation is 0.80%. We definitely confirmed that the muon neutrino flux of the GeV energy region decreased after traveling 250 km. The standard model neutrino hypothesis is excluded with 98.4%C.L..

If we assume this deficit of the number of neutrino events is caused by the $\nu_\mu \rightarrow \nu_\tau$ neutrino oscillation, the most probable combination of $(\sin^2 2\theta, \Delta m^2)$ in physical region is $(1.0, 7.0\times10^{-3})$. At this point, the expected number of neutrino events at SK is 4.18, and probability of the case that we have 3 events is 18.2%.

Acknowledgements

I would like to express my great appreciation to my adviser, Professor A.Suzuki for introducing me to neutrino experiment. I acquired a great interest in the neutrino physics by his guidance. I would also thank him for supporting and guiding me throughout my graduate career.

I would like to show my appreciation to Professor K.Nishikawa as a spokes-person of K2K collaboration. His advise and encouragement were helpful for my thesis. He taught me a lot of things which are useful for my work. Without his help, I would never accomplish my thesis.

K2K benefits from the excellent leadership of its co-spokespersons Prof. Y.Totsuka, Prof. K.Nakamura and Prof. Y.Suzuki. They gave me advice and encouraged me in many cases.

The analysis presented in this thesis depends on the hard works of many people in the K2K collaboration: Prof. K.Kaneyuki, Prof. Y.Itow, Dr. M.Miura, Mr. S.Nakayama and Mr. S.Yamada from ICRR, Prof. M.Sakuda, Dr. Y.Oyama, Dr. T.Ishida, Dr. T.Kobayashi and Dr. Y.Hayato from KEK, Prof. T.Hara, Prof. S.Aoki, Dr. At.Suzuki, Dr. M.Kohama and Mr. T.Iwasita from Kobe University, Dr. T.Nakaya, Mr. H.Yokoyama, Mr. S.Mukai and Mr. A.Shima from Kyoto University, Mr. M.Yoshida from Osaka University, Mr. T.Kadowaki and Ms. H.Yokoyama from Science University of Tokyo and the members in USA, especially, Prof. C.K.Jung, Dr. J.Hill, Dr. W.Gajewski and Dr. S.Mine. I wish to express my special gratitude to them. I would like to thank especially for Dr. T.Ishii for his careful reading of manuscript.

I also thank to members of KEK beam channel group: Prof. M.Takasaki, Prof. K.H.Tanaka, Prof. M.Ieiri, Dr. H.Noumi, Mr. Y.Suzuki, Mr. Y.Yamanoi, Mr. Y.Katoh, Mr. M.Minakawa and Ms. E.Kusano. They gave me many suggestions for the construction of pion monitor and educations for beam properties. Without their helps, pion monitor would never be accomplished.

I am thankful to all people who maintains the 12 GeV Proton Synchrotron at KEK and Super-Kamiokande for the great effort to lead K2K experiment be successful. They gave us the pioneering long baseline neutrino experiment.

I should thank Mr. T.Inagaki for his work. I never forget hard but exciting days for the construction of K2K with him. He gave me many supports for my work.

Finally, I wish to express my deep gratitude to Dr. T.Hasegawa who is the leader of the K2K beam monitor group. His education, guidance and comments made this thesis completed.

Contents

List of Figures

List of Tables

Chapter 1

Introduction

The standard model[1, 2, 3] defines neutrino mass to be zero. Various experimental explorations have been performed to search for neutrino mass since the 1930's, when Pauli[4] predicted the existence of neutrino. The measurements are classified into three: (1)direct measurements, (2)$\beta\beta$ decay measurements, (3)neutrino oscillation measurements.

Direct measurements have been performed for three neutrino flavors, ν_e, ν_μ and ν_τ. For ν_e, the end point of the energy spectrum of the β decay electron is measured. In the process,

$$(Z, A) \longrightarrow (Z+1, A) + e^- + \bar{\nu_e},$$

the maximum electron energy must be E_{max}=m_i-m_f-m_e-m_ν, where m_i, m_f, m_e and m_ν show the masses of the initial nucleus, final nucleus, electron and neutrino, respectively. There have been many experiments using tritium β decay, which give upper limits of ν_e mass to be 2.5 eV[5]. But the fact that most of them give negative best fit values for the neutrino mass squared means there can be still unknown systematic errors in these measurements[6]. For ν_μ, the mass has been searched for using 2-body π decay at rest, $\pi \rightarrow \mu + \nu_\mu$. The given upper limit is 170 keV[7]. For ν_τ, the upper limit of the mass is given employing multi-body τ decay, $\tau \rightarrow 4(5)\pi + \nu_\tau$. This gives an upper limit of 18.2 MeV[8].

Neutrino-less $\beta\beta$ decay occurs only when the neutrino is its anti-neutrino. In other words, neutrino is a Majorana particle[9] . In this measurement, one measures the rate of neutrino-less $\beta\beta$ decay process,

$$(Z, A) \longrightarrow (Z+2, A) + 2e^-.$$

This decay rate is proportional to the weighted average of the heavy Majorana neutrino mass, $\langle m_\nu \rangle$. This phenomenon has never been observed, and the upper limit of the mass is obtained to be $\langle m_\nu \rangle$ $<$ 0.2 eV[10].

As a consequence of (1) and (2), only upper limits of neutrino mass have been given. These upper limits confirm that neutrino mass is very small and close to zero, even if it exists.

Neutrino oscillations were proposed by Z.Maki, M.Nakagawa and S.Sakata[11], and by B.Pontecorvo[12]. If the mass eigenstates of neutrinos are different from the weak eigenstates, the probability that the flavor α neutrino transforms to the flavor β after traveling distance L(km) is expressed by following formula:

$$P(\nu_\alpha \rightarrow \nu_\beta) \quad = \quad \sin^2 2\theta \ \sin^2\Big(1.27\Delta m^2 \frac{L}{E}\Big), \tag{1.1}$$

where, E shows the neutrino energy(GeV) and Δm^2(eV^2) shows the difference of the mass eigenvalues squared: $\Delta m^2 = m_2^2 - m_1^2$. Once the existence of neutrino oscillations is established, it means the neutrino mass is finite and lepton number is violated. This method is sensitive to very small Δm^2 if the proper distance L is chosen although this cannot measure the mass of the neutrino itself.

Regarding the neutrino oscillations, we have a strong indication from the atmospheric neutrino observation by the Kamiokande experiment. Atmospheric neutrinos are created in the atmosphere as follows. The interaction of primary cosmic rays from the universe with the atmosphere creates secondary pions and kaons. When the pions and kaons decay to muons, muon neutrinos are produced. Further, muon decay generates an electron neutrino and an (anti) muon neutrino. The ratio of muon neutrinos to electron neutrinos is reliably calculated by a Monte Carlo simulation (MC). An anomaly in the measured flavor ratio for atmospheric neutrinos was first recognized by the Kamiokande experiment[13]. IMB[14] and Soudan-II[15] experiments confirmed it. Table 1.1 shows the results of the atmospheric neutrino measurements. The observed lepton flavor ratio of numbers of events, (muon/electron), is compared to the ratio expected from MC predictions. These results clearly show that the muon neutrino flux decreases and/or the electron neutrino flux increases. Moreover

	detector type	kt · year	$R(\nu_\mu/\nu_e)_{obs}/R(\nu_\mu/\nu_e)_{MC}$
Kamiokande (sub-GeV)	Water Cherenkov	8.2	$0.60^{+0.06}_{-0.05}$(stat.) $\pm$ 0.05(sys.) [13]
Kamiokande (multi-GeV)			$0.57^{+0.08}_{-0.07}$(stat.) $\pm$ 0.07(sys.)[13]
Super-Kamiokande (sub-GeV)	Water Cherenkov	33	0.63 $\pm$ 0.03(stat.) $\pm$ 0.05(sys.) [16]
Super-Kamiokande (multi-GeV)		33	0.65 $\pm$ 0.05(stat.) $\pm$ 0.08(sys.) [16]
IMB3	Water Cherenkov	7.7	0.54 $\pm$ 0.05 $\pm$ 0.012 [14]
Soudan-II	Iron calorimeter	3.9	0.64 $\pm$ 0.11 $^{+0.06}_{-0.05}$[15]

Table 1.1: Summary of the measured R(μ/e) value of atmospheric neutrino experiments

Kamiokande showed an impressive zenith angle distribution of the double ratio in the multi-GeV energy region[13], as shown in Fig. 1.1. Fig. 1.2 shows the definition of the zenith angle. We can explain these phenomena by introducing neutrino oscillations with the parameters shown in Fig. 1.3[13]. This is a strong indication for neutrino mass and lepton mixing. Super-Kamiokande also measured the ν_μ/ν_e ratio to be smaller than predictions, as shown in table 1.1[16]. Their zenith angle distributions are shown in Fig. 1.4 along with MC expectations with and without neutrino oscillations[16]. Super-Kamiokande collaboration declared that they found an evidence for ν_μ oscillation based on these data.

This hint strongly urged us to study neutrino oscillations using an accelerator. The neutrino oscillation parameters ($\sin^2 2\theta$,Δm^2) suggested by the atmospheric neutrino measurements, (1.0, $10^{-3} \sim 10^{-2}$), are in reach if we set L/E of the experiment to be $10^2 \sim 10^3$ (from Eq. 1.1). In the accelerator experiments, the neutrino flux and their flavor is well known (almost pure muon neutrinos). Thus we can confirm the existence of neutrino oscillations very clearly.

In order to achieve this plan, we proposed[17] and are performing the KEK to Kamioka long baseline neutrino experiment (K2K). This is the first experiment in the world which has an earth scale baseline using an accelerator. In this experiment, L=250 km, $\langle E_\nu \rangle$=1.3 GeV and resulting L/E is roughly 200. Fig. 1.5 shows a schematic view of the K2K. Since the neutrino beam diverge after a long baseline, a far detector must be massive. Super-Kamiokande(SK) is quite proper for this purpose. We also have near detectors and secondary beam monitors inside KEK in order to measure the neutrino beam characteristics just after its generation.

In this experiment, the distance from the neutrino creation point to the detection point is fixed. Therefore we can see a clear oscillation pattern if we measure the neutrino energy precisely. Fig. 1.6 shows the expected oscillation patterns in two sets of typical neutrino oscillation parameters. The top figures show the probability of neutrino oscillations as a function of energy. The middle ones show the distortion of the neutrino flux at SK. The histogram shows the MC expected neutrino flux (units are "number of neutrinos/cm^2/10^{20}POT(Proton On Target)"). The shaded one is the expected flux times probability. The bottom ones show the neutrino flux times the total cross section of neutrinos on water, which corresponds to the total expected number of events at SK. Distortion of the observed neutrino energy spectrum is definite evidence for the neutrino oscillation. In this thesis, we discuss the neutrino oscillation using K2K data taken during 1999. Because of small statistics, only the total



Figure 1.1: Zenith angle distribution of R(μ/e) in the multi-GeV energy range by Kamiokande [13]. The histogram shows the Monte Carlo prediction with neutrino oscillations with parameter sets ($\sin^2 2\theta$,Δm^2) corresponding to $\nu_\mu \leftrightarrow \nu_e$ ((1.0,1.8$\times 10^{-2}$),dashes) and $\nu_\mu \leftrightarrow \nu_\tau$ ((1.0,1.6$\times 10^{-2}$),dots) oscillations.



Figure 1.2: Neutrino flight length as a function of zenith angle, $\cos\theta$. The definition of zenith angle is also shown. $\cos\theta$ = -1 corresponds to upward-going and $\cos\theta = 1$ corresponds to downward-going.



Figure 1.3: 90% C.L. allowed oscillation parameters ($\sin^2 2\theta$, Δm^2) for $\nu_\mu \leftrightarrow \nu_e$ (left) and $\nu_\mu \leftrightarrow \nu_\tau$ (right) oscillations[13]. Shaded regions show the allowed region by Kamiokande sub-GeV and multi-GeV data.



Figure 1.4: Zenith angle distribution of μ-like and e-like events for sub-GeV and multi-GeV data sets[16] by the Super-Kamiokande. Upward-going particles have cos$\Theta \leq 0$ and downward-going particles have cos$\Theta \geq 0$. Sub-GeV data are shown separately for p$\leq$400 MeV/c and p$\geq$ 400MeV/c. Multi-GeV e-like distributions are shown for p$\leq$2.5 GeV/c and p$\geq$2.5 GeV/c and the multi-GeV μ-like are shown separately for FC(Fully Contained in the fiducial volume of the Super-Kamiokande detector) and PC(Partially contained in the fiducial volume of the Super-Kamiokande detector) events. The hatched region shows the Monte Carlo expectation for no oscillations normalized to the data live time with statistical errors. The bold line is the best fit expectation for $\nu_\mu \longleftrightarrow \nu_\tau$ oscillations with the overall flux normalization fitted as a free parameter.



Figure 1.5: Schematic view of K2K



Figure 1.6: Neutrino energy spectrum distortion in the K2K in two Δm^2 cases. (Δm^2=0.01 (Left) and Δm^2=0.005 (Right), $\sin^2 2\theta$=1) In both the left and right figures, the top figure shows the probability of neutrino oscillations as a function of energy. The middle one shows the distortion of the neutrino flux at SK. The histogram shows the MC expected neutrino flux (units are "number of neutrinos/cm^2/10^{20}POT(Proton On Target)"). The shaded one is the expected flux times the probability. The bottom ones show the neutrino flux times the total cross section of neutrinos on water, which corresponds to the total expected number of events at SK.

number of neutrino events are used for the oscillation analysis instead of the energy spectrum.

In chapter 2, the key issues for the K2K are described. In chapter 3, we will describe the set-up of the K2K. In chapter 4, the hardware details of the muon monitor and the pion monitor are described. In chapter 5, Monte Carlo simulations which are used in this experiment are described. Further, we describe the measured properties of the neutrino beam, using the muon monitor (chapter 6), using the pion monitor (chapter 7) and using the near detector (chapter 8). Chapter 9 describes the way to get the expected number of neutrino events at SK. And chapter 10 describes the observation at SK. Finally we compare expected and observed number of neutrino events at SK. Its implication for the neutrino oscillation hypothesis is also discussed.

Chapter 2

Key Issues for KEK-Kamioka Long Baseline Neutrino Experiment (K2K)

As shown in Fig 1.5, K2K is the first experiment in the world which has an earth scale baseline using an accelerator. Therefore we have first trials to achieve this experiment, as follows;

1. Determination of the neutrino beam direction from KEK to SK with a few mrad precision.
2. Timing synchronization between KEK and Kamioka.
3. Prediction of the neutrino flux at SK based on the KEK measurement.

2.1 Precise Neutrino Aiming from KEK to Kamioka

2.1.1 Beam Direction Survey Employing Global Positioning System(GPS)

Beam-line at KEK has to be constructed with a correct direction in order to shoot SK with the neutrino beam. For this goal, in the construction of the beam-line, the ideal schedule would be that: (1) one defines the position of the production target, (2) measures positions of the target and SK to know the beam direction, (3) define the beam-line, (4) constructs the beam-line tunnel and places the beam-line elements along the beam-line, although it was parallelly processed in reality. Item (2) is the most difficult hurdle in these processes.

Strictly speaking, our job to achieve (2) is to know the latitude, longitude and height above the sea of the target at KEK and the SK detector. One may utilize the geodetic network, constructed so far by Geographical Survey Institute (GSI) with standard optical surveying and leveling, where one make local surveys independently at KEK and SK with referring to the nearest triangulation points. However it is known that the network has integrated distortion [18].

Thus we use GPS system to do this. This way is most reliable and indispensable at present [19].

GPS system consists of 27 operational satellites of US Naval Observatory (USNO). Each satellite contains an atomic clock system; satellites emit the timing signals from it. Moreover they also emits their own positions at the same time. The atomic clocks inside the satellites are monitored and calibrated using USNO Master Clock periodically. Orbits of the satellites are also calculated and renewed periodically. A GPS receiver installed on the ground receives the signals from 4$\sim$6 satellites simultaneously. It measures its own position (latitude and longitude and hight above the sea) and timing accurately.

We surveyed both the target position and SK using GPS receivers. A GPS receiver know its own position as explained above. However we use a relative measurement of GPS receivers since it can cancel out most of systematic errors* . We defined the origin at a triangulation point at KEK. And

* Relative measurement allow to measure both positions with a few mm precision, though a GPS receiver alone with precision of a 10 meter order. Cancelable errors are 1)the precision of the orbit of GPS satellite, 2)the condition of ionosphere and atmosphere, 3)the noise of the receiver and so on.

we transfered the survey point step by step, like KEK→Kamioka Town→Kamioka mine→SK. Except the final survey step, we surveyed each point using GPS. Final survey cannot use GPS system since SK is located 1000 meter underground in the Kamioka mine. SK survey was performed using normal optical survey and leveling from the entrance of the mine to the GPS surveyed points.

Reference[19] describes the details and the results of this measurement. Final positions of target at KEK and SK with global ellipsoidal coordinate system, WGS-84[20] are summarized in table 2.1.

	Latitude	Longitude	Height above the sea
Target at KEK	$36°09'14.9531''$(N)	$140°04'16.3303''$(E)	70.218m
SK	$36°25'32.5862''$(N)	$137°18'37.1214''$(E)	371.839m

Table 2.1: The positions of target at KEK and SK

As the results of this survey, direction of our beam-line was defined. For example, bending angle to the underground is $1°04'30''$.

We estimated the error of this direction, by GPS position reproducibility test after the construction of the beam line. According to this results, the error of the beam direction is less than 0.1 mrad. It is 10 times better than the physics requirement. We cleared the first barrier of the K2K requirement.

2.1.2 Experimental Proof of Neutrino Beam Aiming

Once beam-line was directed correctly, steering the beam and checking the direction of beam become essential.

We have two systems to check the neutrino beam direction. One system is the muon monitor to monitor muons which are the particles of decayed partner of neutrinos in the beam-line. The other is near neutrino detector, which detect the neutrino induced events directly.

The muon monitor has the advantage of being able to check the beam direction spill by spill since the muon intensity is high. This is the only way to check the stability of the beam direction in spill-by-spill basis, and to steer the beam during beam tuning. On the other hand, measuring the neutrino events takes long time to accumulate significant statistics. It is not useful for the beam tuning. However the validity of the beam direction tuned by muon distribution must be confirmed by neutrino distribution itself.

Location and set-up of these detectors will be described in chapter 3 and 4.

2.2 Timing Synchronization between KEK and Kamioka by GPS

Generally speaking, a ratio of signal to noise (S/N) of the neutrino experiment is small since cross section for neutrino is quite small. Therefore neutrino experiment uses the fast extracted beam from the accelerator, and get better S/N ratio employing the timing information. The timing information is indispensable for this experiment particularly because 250 km long baseline reduces the neutrino flux much.

We achieved the fast extraction of the beam successfully[21]. As a result, we have the potential of $\sim 10^6$ gain for S/N since our spill has 1.1 μs time length per 2.2 sec repetition. The remaining thing to do is to link the timing information from KEK to SK

We cannot connect KEK to SK using normal cables. Thus we employ the GPS system again to achieve this. As described in the section before, a GPS receiver can get absolute timing information on the earth in principle.

We installed GPS receivers both at KEK and SK for synchronization. These are non-military GPS receivers, nevertheless it can measure the time with 100 ns accuracy† . Beam firing time is recorded in the beam-monitors data at KEK. Furthermore we record the time information on each

† From 2000, we can get more accurate timing information thanks to the decision of the American government.

event at SK. Then we can identify the events associated with beam. Actually we measured the timing difference between GPS receivers at KEK and SK by moving atomic clock. As a result, difference $|T_{KEK}\text{-}T_{SK}|$ is 115±273 ns[‡] . This shows GPS receivers give reasonable time information.

Reduction factor of background events is 10^{-6} level using this strategy as planned. Event rate induced by atmospheric neutrinos are about 8 events/day; This rate becomes negligibly small comparing to beam associated events after the timing cut.

2.3 Prediction of the Neutrino Properties at Kamioka by means of Measurement at KEK

2.3.1 Measurement by Near Detector

A near detector is located at 300 meter from the target. This detector measures the flux and the spectrum of the neutrino beam just after its creation. This information is used to predict the neutrino flux at SK.

2.3.2 Measurement by Pion Monitor

K2K would be much easier if neutrino source were a point like. Because, in this case energy spectrum at the near detector is same as SK, and intensity is reduced as a function of $1/r^2$ (r:distance from source to detector). However actual source is not point like. Strictly speaking, from SK the neutrino source is regarded as a point, but from the near detector it cannot because of too short distance between the source and the detector (100~300 meter). Fig. 2.1 shows the schematic view of this situation. The near detector feels the length and the width of the decay pipe.



Figure 2.1: The schematic view of our beam

This means the energy spectrum at the near detector is different from SK and the intensity is not proportional to the $1/r^2$. In other words, the near detector information of the event number and energy spectrum is not enough to predict the neutrino flux at SK. Fig. 2.2 shows the neutrino

‡ Error comes from our atomic clock





Figure 2.2: The average neutrino flux in 3m radius in various r positions and deviations from the expected $1/r^2$ rule

intensity in 3 meter radius in various distances from the target and deviations from the expected $1/r^2$ rule.

Needless to say, we have MC simulation to do it. But we have an large uncertainty of pion production model at the target in the simulation; Pion is the source of neutrino. This limits the simulation ability. We must reduce this uncertainty using other methods as much as possible.

To solve this problem, we designed a pion monitor. This detector measures the angle and the momentum of pions before the decay tunnel to know the property of neutrino sources. Because of the MC free analysis of the pion monitor, we do not have any problems even if real pion production is different from one used in the MC. Using this knowledge, we can predict the neutrino energy spectrum at an arbitrary distance.

Principles and designs of this detector will be described later.

2.4 Stability of neutrino beam

The stable quality: intensity, direction and spectrum, of the neutrino beam is indispensable for the K2K. They are proved by the secondary beam monitors and the near detector, as explained later.

Chapter 3

Experimental Set-up of K2K

The setup of the K2K consists of the KEK site and the Kamioka site, which are apart each other by 250 km. Schematic view of whole K2K is already shown in Fig. 1.5. Fig. 3.1 shows components of this experiment inside KEK in detail.



Figure 3.1: Setup in the KEK site consisting of the 12 GeV Proton Synchrotron, neutrino beam-line and near detector.

The neutrino beam-line to generate the neutrino beam and the near detector to measure the characteristics of neutrino beam are located inside KEK.

3.1 Horn Focused Wide Band Neutrino Beam Line at KEK

K2K has the following components as the beam-line as shown in Fig. 3.1.

1. KEK 12 GeV Proton Synchrotron(PS)

2. Proton extraction line

3. Horns (Magnet/Target)

4. Decay tunnel
5. Monitors

In this section, each component of this neutrino beam-line in Fig. 3.1 is described. ([22])

3.1.1 KEK 12 GeV Proton Synchrotron(PS)

Fig. 3.2 shows a schematic view of 12 GeV Proton Synchrotron. (Direction of this figure is different from Fig. 3.1.) The proton beam is extracted to the neutrino beam-line from the "EP1" beam channel.



Figure 3.2: Schematic view of the 12 GeV Proton Synchrotron

Protons are accelerated by the following procedures:

- extraction of negative ions from an ion source,
- acceleration by a 750 keV Cockroft-Walton Accelerator,
- acceleration by a 40 MeV Alvarez-type LINAC,
- conversion of negative ions to positive ones with a carbon film,
- acceleration by a 500 MeV Rapid-Cycle Booster Synchrotron,
- acceleration by the 12 GeV Proton Synchrotron.

Accelerated protons are extracted from the 12 GeV PS in a fast extraction mode (Repetition: 2.2 sec, Spill :1.1 μsec). The micro-structure inside a single spill corresponds to the harmonic number of the main ring which is 9. As shown in Fig. 3.3, we can observe this micro-structure using Current Transformers(CTs: which we describe later) after extraction. For more details, see [23, 21].



Figure 3.3: Oscilloscope photograph of the micro-structure in the beam

3.1.2 Primary Proton Beam Transport Line

We have a kicker magnet for the fast extraction at the extraction point of the accelerator. Kicker, septum, and bump magnets lead the proton beam to the neutrino beam-line [21]. Fig. 3.4 shows the neutrino beam-line after the extraction.

The proton beam direction is toward the north just after the extraction point and it must be bent towards Kamioka employing the results of survey (about 90° to the west). An arc section of the beam-line, which consists of 18 bending magnets and 18 quadrupoles, meets that request.

The target station was built after the arc section. The proton beam is finally focused on the neutrino production target at the target station. A steering magnet is placed just before the target to direct proton beam to SK, about 1° downward from the level of the production target (Fig. 5.1).

We use TRANSPORT[24] and DECAY-TURTLE[25] program to optimize the beam-line optics [19]. Thanks to this optimization, the actual transport efficiency of this beam-line is about 85%.

3.1.3 Horn Magnets and Target

There are two magnetic horns in the target station to efficiently focus the pions, the parent particles of neutrinos. Figs. 3.5 and 3.6 show the schematic view and the photograph of the two magnetic horns. The first horn has dimensions of 2.37 meter in length, and 0.70 meter in diameter. The second horn has dimensions of 2.76 meter in length and 1.65 meter in diameter, located 8 meter downstream of the first horn. It is needed to efficiently increase the neutrino flux in the forward direction since the momentum distribution of the secondary pions is wide (from 0 to 10 GeV/c).

Due to the low-energy feature of our experiment, our design is such that the target is inside the 1st horn in order to focus pions more efficiently. The horns and the target are made from Aluminum alloy. The target is 66 cm long and 20 mm in diameter in June, 30 mm in November. This length corresponds to 1.5 interaction lengths. MC simulation shows almost all protons interact* with the target thanks to the magnetic field inside the horn.

In contrast, other parts of the horn through which the secondary particles pass, are required to be as thin as possible in order to minimize the absorption losses of pions. Thus we designed and manufactured horns carefully so as to have mechanically enough strength to stand the electromagnetic force and thermal expansion.

We drive the horns every 2.2 sec with a 2 ms long 250 kA pulsed current like Fig. 3.7. We need to synchronize them with the fast extracted beam (1.1 μs bunch width) to generate the toroidal magnetic fields with respect to the beam axis [26]. We cannot use DC current because no power

* include elastic scattering



Figure 3.4: Schematic view of the neutrino beam-line and near detector, after 12 GeV-PS



Figure 3.5: Schematic view of the horns.



Figure 3.6: The photograph of the horns.

supply can provide 250 kA. Even if such a power supply exists, the horns could not dissipate the heat.

According to the calculation, the strength of the magnetic field B(kGauss) at R(cm) distance from beam center is given by;

$$B = \frac{I}{5.0 \cdot R}, \tag{3.1}$$

where I is the current supplied to the horn magnets in units of kilo-ampair. Hence we have 50 kGauss at R=1 cm. (This formula is correct in the air part of horn)

Fig. 3.8 shows the capability of our horn system. The Shaded region shows the MC simulated neutrino flux at SK with the horn current of 0 A, and the histogram shows that of 250 kA (target is 30 mmϕ). The simulated neutrino flux above 0.5 GeV using 250 kA current supplied to the horn magnets is about 22 times more than that of 0 kA.

Various measurements have been done to know the characteristics of this horn system. For example, magnetic field measurements using coil, performance test of the cooling system, and so on. These are summarized in [27, 28].

The measured radial dependence of magnetic field is consistent with the calculation [27]. However, we found some azimuthal direction dependence on magnetic field strength [28] like Fig 3.9. This causes some systematic error on the K2K analysis. It will be discussed later.

We must take the different beam conditions in June and November into account because our 1st horn was changed. We changed the diameter of the target part of the 1st horn in diameter from 20 mm ϕ to 30 mm ϕ in order to strengthen the weakest part against the electromagnetic force. Thus we can also change the current supplied to the horn magnets from 200 kA to 250 kA thanks to this building-up.

3.1.4 Decay Tunnel

The lifetime of pion: 2.6×10^{-8} sec ($c\tau$ = 7.8 m) is prolonged by a Lorenz factor.



Figure 3.7: The pulsed current supplied to horn magnets[27]



Figure 3.8: Capability of our horn system. The shaded histogram shows the MC simulated neutrino flux at SK with the current supplied to the horn magnets of 0 kA, and the histogram shows with that of 250 kA. (target is 30mm ϕ)



Figure 3.9: Measured horn magnetic field

In order to make pions decay to neutrinos efficiently, we designed a 200 meter long decay tunnel which has a radius of 0.75, 1.0 and 1.5 meter. Fig. 3.10 shows the schematic view of decay pipe of this experiment.

The muon monitor is installed after the beam dump to monitor the beam direction and intensity. It is described later (chapter 4).



Figure 3.10: Schematic view of the decay pipe.

The decay pipe is filled up with helium gas because the interaction length of helium gas is about 5 times longer than air. (Interaction length of helium: 3.64 km(STP), that of Air: 0.731 km(STP)). It is also important to reduce the number of neutrinos produced in the gas which may cause uncertainty in this experiment.

3.1.5 Primary Beam Monitors

Current Transformer (CTs)

CT is a kind of coil sensitive to the beam current. The schematic view of CT is shown in Fig. 3.11.



Figure 3.11: Schematic view of the CT

There are 13 CTs in the primary beam-line (Table 3.1). They are used as proton beam intensity monitors at various points. Comparison of these CT values gives information on the transport efficiency (= down stream intensity/ upstream intensity). The efficiency in the first run time is typically ~85% from the extraction point to the target.

Each CT is calibrated using pulse current and beam as well. The absolute proton number is known within 10%.

Segmented Plates Ionization Chambers (SPICs)

SPICs are used for the profile measurement of the primary protons. There are 28 SPICs in the beam-line from the extraction point to the entrance of the decay pipe (Table 3.1). The principle of ionization chambers is shown in Fig. 3.12



Figure 3.12: The principle of the ionization chamber

Filled gas in the detector is ionized by radiation. Created electrons (or positively charged ions) are gathered at the anode (or cathode) . Finally collected electrons (ions) can be taken as the electric signal. General properties of ionization chambers are described in [29].

The SPICs used in the K2K have segmented anode to measure the particle density in a place normal to the beam like Fig. 3.13.

It consists of three copper sheets with thickness of 28 μm. The central one is for the cathode plane (-HV), and the others are for horizontal and vertical readout cathode (GND) planes. The readout planes have 32 channels for x and y readout. The proton beam directly hits this chamber, thus this copper is as thin as possible. Most of(26 out of 28) the chambers have a 5 mm pitch stripe, except one chamber before the target which has a 1.27 mm pitch, and one chamber before the decay pipe which has a 2 cm pitch. These monitors are quite useful for the steering of the beam. The SPICs



Figure 3.13: Schematic view of the SPIC used in the K2K.

used in KEK are described in [30].

Fig. 3.14 show the online display for beam-line monitors. English characters shows the monitor name; i.e. "V39 out" means the monitor located downstream of 39th vertical dipole magnet.

Table 3.1 summarizes name, type and the purpose of the beam-line monitor.

The apparatus of the muon monitor and the pion monitor are described in the next chapter.

Beam-line DAQ

As shown in Fig. 3.14, we prepare lots of monitors in the beam-line. We must change analog signals from these monitors to digital ones using electronics and computers.

Fig. 3.15 shows the beam-line DAQ system.

We need only charge information from these monitors, such as CTs or SPICs. Therefore we use normal charge-sensitive-type Analog-to-Digital Converters(ADCs) as front-end electronics. These ADCs are sensitive to the charge from 0.25 pC to 1000 pC typically.

The 12 GeV PS accelerator RF distributes the trigger signal for the DAQ. This timing is 1.1 ms earlier than the real beam. We use this signal after some adjustment. This timing is also used for horn firing. Further we make a dummy trigger pulse 1 sec after the real trigger to take the pedestal data. Gate widths for these ADCs are as follows:

1. about 1.2 μs for CT: this is as narrow as possible so as not to pick up the noise,

2. 2.0 μs for SPIC: This is for the drift time of electron.

3. 2.0 μs for muon monitor: Same reason as SPIC. Please see chapter 4 for more details.

We use 6 Personal Computers(PCs) as front-end DAQ machines. Each PC takes the digital data from electronics via PC-CCPbus interface system. Six PCs are to cover the total of about 400 meter of beam-line length. We divide the neutrino beam-line into the following 4 sections for convenience. 1)North Counter Hall, 2)near the Arc, 3)Target Station and 4)Muon pit. PCs are divided as shown in Fig. 3.15 to collect data efficiently. Finally one host PC gathers this information by means of 100 Mbyte/sec Ethernet.

In addition to the charge information, GPS data for beam firing time is taken by the VME module in the North Counter Hall. This is because the GPS receiver is installed there.



Figure 3.14: Monitors in the neutrino beam-line



Figure 3.15: Beam-line DAQ system

Characters	monitor type	purpose	comment
EP1 in	CT,SPIC	intensity monitor and steering	5mm pitch
q01 in	SPIC	steering	5mm pitch
q01 out	SPIC	steering	5mm pitch
Col. out	SPIC	steering	5mm pitch
q11 in	CT,SPIC	intensity monitor and steering	5mm pitch
b12 out	SPIC	steering	5mm pitch
q12 in	CT,SPIC	intensity monitor and steering	5mm pitch
K5 target	CT,SPIC	intensity monitor and steering	5mm pitch
BS3in	SPIC	steering	5mm pitch
q15-q16	SPIC	steering	5mm pitch
K6 target	SPIC	steering	5mm pitch
q18 in	SPIC	steering	5mm pitch
q31 in	SPIC	steering	5mm pitch
vd1 in	CT,SPIC	intensity monitor and steering	5mm pitch
q37-q38	SPIC	steering	5mm pitch
h32 in	CT,SPIC	intensity monitor and steering	5mm pitch
q45 out	SPIC	steering	5mm pitch
q49 in	CT,SPIC	intensity monitor and steering	5mm pitch
q53 in	CT,SPIC	intensity monitor and steering	5mm pitch
q57 in	SPIC	steering	5mm pitch
q59 in	CT,SPIC	intensity monitor and steering	5mm pitch
q61 in	SPIC	steering	5mm pitch
q65 in	CT,SPIC	intensity monitor and steering	5mm pitch
q68 in	SPIC	steering	5mm pitch
h37 in	CT,SPIC	intensity monitor and steering	5mm pitch
v39 out	SPIC	steering	5mm pitch
target SPIC	CT,SPIC	intensity monitor and steering	1.27mm pitch
HORN1, HORN2	slow monitor	monitor horn current	
PION	Cherenkov counter	measure pions	described later
IONO	Ion Chamber	measure secondary particles	
P/PI	SPIC	measure secondary particle profile (projection)	2cm pitch
MUON	SI + IC	measure muon direction and intensity	described later

Table 3.1: Name, type and purposes of beam-line monitor. Please refer to Fig. 3.14.

3.2 Near Detector at KEK

As shown in Figs. 3.1 and 3.4, the near detector is located 300 meter from the target, the experimental hall is 24 meter in diameter and 16 meter in depth.

Fig 3.16 shows the schematic view of the near detector at KEK. From upstream to downstream are the 1 kilo ton water Cherenkov detector[31], the Scintillating Fiber Tracker[32], the Lead Glass Calorimeter[33] and the Muon range detector[34].

One kilo ton water Cherenkov detector is to check the analysis techniques of water Cherenkov detectors and to measure neutrino-water cross section. The Scintillating Fiber Tracker is to study neutrino interactions with its fine granularity. The lead glass calorimeter is to measure electromagnetic component in an event.



Figure 3.16: Schematic view of the near detector at KEK

The muon range detector is used to measure neutrino properties, for example intensity, profile and energy. The event rate measured by the muon range detector is used to calculate the expected number of neutrino events at the far detector. In this thesis, only the data of the muon range detector is used as the data of the near detector.

3.2.1 Muon Range Detector

This system consists of vertical and horizontal drift-tube layers interleaved with iron absorber. The energy of the muons is measured by the range method. The size of the layer is about 7.6 m $\times$ 7.6 m. We use 4 iron plates of 10cm thickness and 8 plates of 20 cm thickness. Total iron thickness of 2 meter covers up to 2.8 GeV muons.

Fig. 3.17 shows the detector. The left figure shows the top view and the right figure shows the side view. In both figures, the left side is upstream of the beam. (opposite direction against Fig. 3.16)

Table 3.2 summarizes the detail order of drift-tube and iron layers.

As shown in Fig. 3.18, 8 tubes make one module. We have modules of various length , from 245 cm to 760 cm. We use 760 cm modules for most drift-tube layers; however, we do not have enough to make all the layers. Therefore for some layers like the 4th horizontal drift-tube layer, we combine 2 short modules to make a layer.



Figure 3.17: The schematic view of muon range detector. Left figure shows the top view and right shows the side view; In both figures, left side is upstream of the beam (opposite direction against Fig. 3.16).



Figure 3.18: The schematic view of one muon drift-tube module [34]

Layer	H×V×t (cm^3)	cm × modules	cm × modules
chamber 1X (V) chamber 1Y (H)		760×25	 760×25
Iron 1	750×763×10		
chamber 2Y (H) chamber 2X (V)		 760×25	760×25
Iron 2	750×763×10		
chamber 3Y (H) chamber 3X (V)		 760×25	760×25
Iron 3	750×763×10		
chamber 4Y (H) chamber 4X (V)		 760×25	(505+245)×25
Iron 4	750×763×10		
chamber 5Y (H) chamber 5X (V)		 760×25	(505+245)×25
Iron 5	750×763×20		
chamber 6Y (H) chamber 6X (V)		 760×25	760×25
Iron 6	750×763×20		
chamber 7Y (H) chamber 7X (V)		 760×25	(290+474)×25
Iron 7	755×780×20		
chamber 8Y (H) chamber 8X (V)		 760×25	(290+474)×25
Iron 8	755×710×20		
chamber 9Y (H) chamber 9X (V)		 760×25	(474+290)×25
Iron 9	755×709×20		
chamber 10Y (H) chamber 10X (V)		 760×25	(474+290)×25
Iron 10	755×709cm×20		
chamber 11Y (H) chamber 11X (V)		 760×25	(300+474)×6+(290+474)×17
Iron 11	755×674×20		
chamber 12Y (H) chamber 12X (V)		 505×25	760×1+(300+505)×16
Iron 12	755×674×20		
chamber 13Y (H) chamber 13X (V)		 505×25	760×1+(300+505)×16

Table 3.2: Arrangement of drift-tube and iron layers in muon range detector. H, V and t means horizontal size, vertical size and thickness, respectively. X and Y means direction of the measurement information; i.e. installation of drift tubes vertically allows us to measure x position of a charged particle.





Figure 3.19: Typical electric field and drift time in the drift tube (calculation[34]) Left: electric field (V/cm) inside the drift tube. Right: drift time (μsec) inside tube.

We use P10(Ar 90% + CH_4 10%) gas for the drift tubes. The typical electric field and drift times of this drift tube are shown in Fig. 3.19. These values are from the calculations in ref.[34]. According to this figure, the maximum drift time of separated electron is about 1 μs.

The signal of the drift-tube is digitized in front-end electronics circuit. In the circuit, the signal is amplified by a factor of 100. A discriminator judges whether the amplified signal is over -30 mV or not and the timing information of the discriminated signal is digitized using 20 MHz clock if it exceeds 30 mV. The TDC dynamic range is 6bits (64 counts). Therefore this electronics covers 64×50 ns=3.2 μs time range. It is enough dynamic range to measure the neutrino induced signal because the spill itself is about 1 μs and the maximum drift time is also about 1 μs. TDC data with hit tube addresses are sent to a TKO[35] Memory module.

From timing information, we can reconstruct the track of a charged particle. The performance test was done using cosmic rays. It shows that we have a spatial resolution of about 2 mm. The performance of this detector is summarized in table 3.3.

Item	Performance
Hit efficiency	99%
Spatial resolution	2 mm
Energy threshold	250 MeV
Energy resolution	150 MeV
Angle resolution	8 degree
Vertex resolution	10 cm

Table 3.3: The detector performance of the muon range detector

3.3 Super-Kamiokande(SK) as a Far Detector

3.3.1 General Description of the Detector

Super-Kamiokande[36, 37] is a ring image type water Cherenkov detector. Super-Kamiokande detects the Cherenkov photons emitted by charged particles which have larger velocity than that of light inside material. Cherenkov photons are emitted along the particle direction with a half cone angle θ_C.

$$\cos\theta_C = \frac{1}{n\beta} \tag{3.2}$$

where, β is defined as $\beta = v/c$. (v is the particle velocity. c is velocity of light.) n is the refractive index of materials. The spectrum of Cherenkov light as a function of wavelength λ is

$$\frac{dN}{d\lambda} = \frac{2\pi\alpha x}{c}\sin^2\theta_c\frac{1}{\lambda^2} \tag{3.3}$$

where, α is the fine structure constant ($\sim 1/137$) and x is the length of the particle trajectory.

The Super-Kamiokande detector consists of about 50000 tons of pure water filled in a cylindrical water tank (diameter 39.3 meter and height 41.4 meter), a water and air purification system, photo-multiplier tubes (PMT), electronics and online data acquisition system, and off-line computer facilities. Fig. 3.20 shows the schematic view of the detector. It is located 1000 meter underground (2700 meter water equivalent) in the Kamioka mine in Gifu Prefecture, Japan.

The reason that the detector is underground is to shield against cosmic ray muons. Compared to ground level, the intensity of muons is reduced by about 10^{-5} at the depth of Super-Kamiokande detector.



Figure 3.20: Schematic view of the far detector, Super-Kamiokande

There are two PMT layers inside the detector. One is inner detector(ID), and the other is outer detector(OD). The diameter, height and volume of inner detector are 33.8 m, 36.2 m and 32 kton respectively.

We have a total of 11460 20″ PMTs inside the ID. Seven thousand six hundred fifty of them are installed on the barrel wall, and the others are installed on the top and bottom wall. Each PMT was installed every 70 cm, and the area, which is insensitive to the photons, was covered by black-sheet to absorb the photons. The photo-cathode coverage is 40%.

The OD covers the ID completely. The thickness of the barrel part of the OD is 2.0 m, and that of the top and bottom part is 2.2 m. The OD has 1885 8″ PMTs. Each PMT was installed at the center of a 60 cm×60 cm wavelength shifter board. This causes efficient photon collection even using a small number of PMTs. Further we cover the board by Tyvek-sheet known as the reflective material to enhance the light collection. The OD plays important role to reduce the background. We can identify the cosmic ray muons which come from outside of SK using the OD. Two meter thickness layer of water prevents gamma rays and neutrons from entering the ID. Another important role of OD is to identify the going out muon events, which has vertex inside the ID but the end point of the track is outside of ID.

The ID and OD are optically separated from each other by black sheet and Tyvek sheet (Fig. 3.21).



Figure 3.21: The schematic view of the frame which supports PMTs in SK

3.3.2 Photomultiplier Tube

Hamamatsu Photonics K.K developed 20″ PMT in cooperation with Kamiokande members originally[38]. The PMTs used in SK are improved from the original Kamiokande ones in some points. The size and shape of 20″ PMT is shown in Fig. 3.22.

The photo-cathode of this PMT is made of bi-alkali(Sb-K-Cs). This is suitable for the Cherenkov photon spectrum in the water. Fig. 3.23 shows the quantum efficiency of this PMT as a function of wavelength of photons. It has a peak around 410 nm, 21%.

This PMT has Venetian-blind type dynode. The bleeder-chain of this PMT is optimized to achieve good timing resolution and photon collection. The averaged collection efficiency is more than 70%. Due to this improvement, the one photo-electron peak is clearly seen and the Transit Time Spread (TTS) is 2.2 ns[39]. Since we know the response of this PMT is uniform in the magnetic



Figure 3.22: Schematic view of 20-inch PMTs used in the inner detector of SK



Figure 3.23: Quantum efficiency of 20-inch PMT as a function of wavelength of photons

field with less than 100 mGauss, we have 26 sets of Helmholtz coils surrounding SK. It achieves our requirement for magnetic field strength. The dark noise of each PMT is typically 3.1 kHz under the gain 10^7. We supply high voltage with -2000 V typically.

The PMTs used in the OD are 8″-R1408 type made by Hamamatsu Photonics. These were once used in the IMB experiment and have been recycled. The wavelength shifter boards surrounding the PMTs are 60 cm$^2\times$ 1.3 cm(t). They absorb the ultra-violet photons and re-radiate blue light to which the PMTs are most sensitive. Due to these board, photon collection efficiency increases to $\sim$60%[40]. The timing resolution of a PMT itself is 11 ns and becomes 15 ns when the wavelength shifter is included. It is sufficient to tag the OD events although it is worse than the ID PMTs.

3.3.3 Water Purification System

Super-Kamiokande is filled with the 50000 tons pure water. It is made from natural water near the detector. The water purification system circulates 50 m^3 of pure water per hour to keep the quality. Quality monitor systems are installed at various places. The purpose of the water purification system is to remove radioactive materials and bacteria. This creates good water transparency. The radioactive materials, in particular ^{222}Rn, are background for the solar neutrino analysis.

Fig. 3.24 shows the water purification system. The solid line shows the main circulation of the water and the dotted line shows supplemental circulation line. The heat exchanger keeps the temperature of the water to be 13°C and prevents the growth of bacteria. The ion exchanger and cartridge polisher remove metal ions such as Ra and Th in the water. The ultra-violet sterilizer kills bacteria in the water. The gas in the water such as oxygen and radon, is removed by the vacuum degasifier and finally the ultra filter(UF) removes small dust with size an order of 10 nm.

After the water purification the concentration of radon which is 10^4 Bq/m^3 in the mine water is reduced to $<$ 10 mBq/m^3 and the light attenuation length is kept to about 100 meter at the wavelength of 420 nm.



Figure 3.24: Water purification system of SK

3.3.4 Data Acquisition System

The top figure of Fig. 3.25 shows the electronics for the ID. This electronics system has two kinds of modules, one is the TKO[35] module and the other is the VME module.



Figure 3.25: Data acquisition system of SK

We have total 48 TKO and 8 VME crates, and they are installed in separated 4 electronics huts. In the central hut, there is a VME module and a TRG module for the global trigger.

The PMT signal is handled by the TKO module at first. This system consists of up to 20 Analog Timing Modules (ATMs)[41], one Go/NoGo(GONG) trigger module and one Super-Controller Header bus interface (SCH) module.

A total of 934 ATMs are used for the ID. Each ATM handles the signals of 12 PMTs. The ATM gives the timing information with 0.3 ns resolution up to a 1.2 μs time range, and the charge information from 0.2 pC to 550 pC. Each channel has a pair of switching Time-to-Analog Converters(TACs) and Charge-to-Analog Converters(QACs). This pair of switching channels allow continuous measurements without dead-time. For example, we can measure muon decay events due to this.

Each channel of the ATM has an amplifier with a gain of 100 and a discriminator. The threshold of this discriminator is 100 mV, corresponding to 0.32 pC. A rectangular signal (width 200 ns and height 11 mV) is generated if the analog signal is over the discriminator threshold. These rectangular pulses from all the hit PMTs are added ("HITSUM" signal) and sent to the global trigger module in the central hut and simultaneously a gate window of 900 ns width is opened to start the time measurement in the TAC and the charge accumulation in the QAC. The QAC accumulates charge in a 400 ns time window and keeps it until the global trigger reaches. If the global trigger does not reach it within 1.3 μs, the stored data in the TAC and the QAC are cleared. However, when the global trigger reaches, charge and timing information are digitized by the ADC and sent via the SCH to the memory (SMP) in the VME module.

Pedestals of the ATMs are measured at an interval of 30 min. Only 1/8 of all the ATMs are measured at once.

The bottom figure of Fig. 3.25 shows the front-end part of this system. It consists of 40 paddle cards, 10 charge-to-digital converters(QTCs), 5 time-to-digital converters(TDCs) and one FASTBUS Smart Crate Controller(FSCC). A paddle card has 12 PMT channels. The signal and high voltage lines are AC coupled. The role of the puddle card is to pick off the PMT signals through a high voltage capacitor.

The QTC module converts the PMT analog signal to an ECL leveled logic pulse. The leading edge of the logic pulse corresponds to the transit time and the width of the pulse corresponds to the charge of the analog signal. Furthermore the QTC module provides the rectangular pulse with 200 ns width and 20 mV height and sends it to the trigger module in the central hut.

LeCroy 1877 Multi-hit Time-to-Digital Converter is used as the TDC module of the OD. One module has up to 96 ECL inputs. This TDC module has a resolution of 0.5 ns/channel. The TDC module serves as a pipeline buffer within 32 μs and digitizes 16 of the latest signals and stores them in memory. We reduce this width to 16 μs to reduce data size. The control and readout of the TDC modules are operated by the FSCC and the stored data is sent to the online machines.

3.3.5 Event Triggering System

We have 3 kinds of triggers for the ID. These are for high energy (HE), for low energy (LE) and super low energy (SLE) events. We have one trigger for the OD. Each of them is triggered by its own level of HITSUM signal independently.

HE is mainly used for the analysis of cosmic ray muon, atmospheric neutrino and proton decay events. This trigger requires more than 31 HITSUM signal coincidence within 200 ns. The trigger rate is 5$\sim$6 Hz. LE is mainly used for the solar neutrino analysis in the 5$\sim$6 MeV energy region. This requires 29 HITSUM signal coincidence. SLE trigger was made to bring down the threshold of the solar neutrino analysis to 4.6 MeV.

OD trigger is employed to cut the background from cosmic ray muons. This trigger requires 19 HITSUM coincidence from the QTC module for the OD. If the OD trigger was generated, it is sent to the TRG module.

A global trigger was generated if any trigger of the above 4 is generated. The data stored in the store module is read through the online workstation.

Chapter 4

Beam Monitors for Secondary Particles

4.1 Muon Monitor

4.1.1 Functionality of Muon Monitor

Location

Muon monitors (Fig. 4.1) are situated in a pit at the downstream of the beam dump. We have two kinds of muon monitors; one is an ionization chamber and the other is a silicon detector. The beam dump is located at the end of the decay pipe. It consists of 3.5 meter thick iron and 2 meter thick concrete. These materials correspond to about 5.5 GeV energy loss for a minimum ionizing particle.

The muon momentum distribution is shown in Fig. 4.2. Before the dump it has a peak at around 2.0 GeV/c. In the dump, muons lose energy of about 5.5 GeV, therefore only 2.1% of the muons are observed by the muon monitors. All the hadrons are absorbed by the dump except low energy neutrons.

In this case, muon monitors measure the properties of high energy pions and neutrinos, indirectly. Fig. 4.3 shows the momentum and angle of the pions, which produce the muons pass through the beam-dump. Distributions before the decay pipe are also overlaid. Muon monitors detect pions which have the angle within 10 mrad and the momentum above 5.5 GeV. Fig. 4.4 shows the momentum of the neutrinos coming from pions shown in Fig. 4.3. Open histogram shows the neutrinos coming from all pions, while shaded one shows those from pions shown in Fig. 4.3. Top; linear scale, bottom; log scale.

Goal of muon monitor

Of monitoring systems such muons, pions and neutrinos, we focus on the purpose of the muon monitor, as follows.

1. To monitor the direction of neutrinos (by means of monitoring the profile of muons) spill by spill.

   Fig. 4.5 shows the radial dependence of neutrino intensity and energy spectrum at Super-Kamiokande (MC).

   This figure shows the beam intensity changes less than 1% within 1 mrad (= 0.25 km distance) from the center thanks to the large decay angle of low energy pions. Energy spectrum is also stable within 1 mrad. Therefore the systematic error of the beam intensity coming from the angle of the beam is estimated to be less than 1% if the direction of the muons is known to better than 1 mrad. This error, further, can be reduced if we employ the near detector information.

2. To monitor the intensity stability of the beam spill-by-spill basis.

   There must be a correlation between the total amount of muons and that of neutrinos. We measure the intensity of muons to monitor the stability of the neutrino beam intensity.



Figure 4.1: Left: the beam dump of the neutrino beam line and the muon monitor pit. Right: schematic view of muon monitors, silicon detectors array (Silicon Solid Detectors(SSD) array in the figure) and ionization chamber (μ-SPIC in the figure)



Figure 4.2: Muon momentum distributions. Top left figure shows the momentum of muons before the beam-dump, top right figure shows that of after the beam-dump, bottom left figure shows muon momentum before the beam-dump for only the surviving muons (MC)



Figure 4.3: Momentum and angle of pions, which produce the muons pass through the beam-dump. Left-top: open histogram shows pion angle after 2nd horn, and shaded one shows pions which produce the muons pass through the beam-dump. Left-bottom: pion momentum. Right: scatter plot of pion angle and momentum for pions which produce the muons pass through the beam-dump.



Figure 4.4: Momentum of the neutrinos coming from pions shown in Fig. 4.3. Open histogram shows the neutrinos coming from all pions, while shaded one shows those from pions shown in Fig. 4.3. Top; linear scale, bottom; log scale.





Figure 4.5: Neutrino profile at Super-Kamiokande (MC) and radial dependence of neutrino energy spectrum. Left: Neutrino profile, unit of the vertical axis are "number of neutrinos/cm^2/10^{20}POT". Right: radial dependence of neutrino energy spectrum.

4.1.2 Hardware Set up of Muon Monitor

Ionization Chamber

The ionization chamber is similar to those in the proton beam-line. Though primary proton beam intensity is about 6.0×10^{12}, the muon yield is only a few $\times$ 10^4/cm^2 level. Therefore, in order to create enough charge to be observable, the ionization chamber for the muon measurement has larger pads, ($\sim$200 cm$\times$5 cm). (Fig. 4.6)

There are three electric planes inside gas vessel. The gas vessel is filled with Ar gas. The structure of this chamber is similar to the SPIC inside the primary beam-line (Fig. 3.13). The readout plane has 36 channels in the horizontal axis and 32 channels in the vertical axis. Since it is difficult to make one large sheet, one plane is divided into 6 sheets with the size of 60 cm$\times$90 cm. A readout stripe in each sheet is connected with an electric code. There are 1$\times$25 cm and 2$\times$15 cm insensitive gaps for horizontal and vertical axis, respectively.

Each gap between the two planes is 1cm whose accuracy is 100 μm guaranteed by the insulated spacer. One minimum ionizing particle generates about 100 ion pairs in this gap when it is filled up with Ar gas [29]. Thus each readout channel has a 100 pC level signal. We can use a normal charge sensitive ADC to read it.

Si detector

In addition to the ionization chamber, silicon detectors are installed for redundancy. A schematic view of the silicon detectors is shown in Fig. 4.7

Seventeen small-pad-type silicon detectors (size: 10 mm$\times$20 mm, depletion layer is 300 μm) are installed horizontally and vertically. Nine large-pad-type ones (size: 34mm $\times$34.5 mm, depletion layer is 375 μm) are installed diagonally. One minimum ionizing particle generates about 2.3×10^4 ion pairs in the small Si pad and 2.9×10^4 ion pairs in the large Si pad.



Figure 4.6: Ionization Chamber inside muon pit



Figure 4.7: Si pad detectors inside muon pit

The small Si pad has about 100 pC level signal and the large Si pad has about 1 nC signal without any amplification.

4.1.3 Calibration of Muon Monitor

Ionization chamber

The calibration of the ionization chamber was performed employing muons in the muon pit (Fig. 4.8).



Figure 4.8: Calibration of the ionization chamber

Each strip of the ion chamber has 5 cm width. The same intensity beam enters the two different strips if it is moved to next strip position. For instance, the left side B strip has the same intensity source as the right side A strip in Fig. 4.8 if beam condition is stable.

The ionization chamber has a mechanical support system to move and an accurate position readout system for this calibration method. It is movable within ± 30 cm in both x and y direction. The accuracy of the readout system is 100 μm. The beam intensity is normalized by the CT.

However, this method has a large error propagation since only the ratios to the next strip can be taken in one movement. Thus the actual calibration method is arranged as follows (y direction is shown only as example):

1. The 32ch are divided into 4 groups (1 group has 8ch: Fig. 4.9 (a))
2. The relative gain ratios of the A to B and C to D are taken using 40 cm moving data. (Fig. 4.9 (b))
3. The relative gain ratio of B to C is taken using 55 cm moving data. (Fig. 4.9 (c))
4. The relative gain of each group is calculated.
5. The relative gain ratio of each channel in each group is taken using 5 cm moving data. (Fig. 4.9 (d), like Fig. 4.8)
6. Finally the relative gain of each channel is calculated.

Fig. 4.10 shows the relative gain obtained for horizontal and vertical directions.

Si detectors

The relative gain of the small Si detectors were measured using an LED light source. A schematic view of this calibration is shown in Fig. 4.11

They were measured one by one using this system. To check the reproducibility of the measurement and the stability of the LED, we periodically measure the same Si detector 9 times. It shows the



Figure 4.9: Calibration of the ionization chamber (actual method)



Figure 4.10: The relative gain of each ionization chamber channel, for horizontal (left) and vertical (right) directions .



Figure 4.11: The gain measurement of the small Si pad detectors



Figure 4.12: Results of the gain measurement of small Si pad detectors

reproducibility is about ± 2.3%. Fig. 4.12 shows this result. These measurements show the relative gain of the silicon detectors is consistent within about six percent.

We calibrated the gain of the large-type Si pad detector using the beam with setting Si pad perpendicular to the beam center (Fig. 4.13).



Figure 4.13: The relative gain calibration of large Si pad detectors

We had a 10% level difference of beam intensity along the beam line because of unstable beam during this calibration. This is because it was performed at a very preliminary stage of this experiment. Thus we quote the error of this relative gain as 10%. Results of this calibration are shown in Fig. 4.14



Figure 4.14: The relative gain of large Si pad detectors

4.2 Pion Monitor

4.2.1 Conceptual Design of Pion Monitor

As described in chapter 2, the aim of the pion monitor is to measure the momentum and the angle of pions after the 2nd horn. Charged pions decay only to a neutrino and a charged lepton after the pion monitor. The decay kinematics are completely known. Therefore we can calculate the neutrino spectrum at an arbitrary distance from pion angle and momentum information.

We use the pion monitor information to extrapolate the KEK neutrino flux to the SK neutrino flux. From the above discussion, the pion monitor can predict the neutrino spectrum at KEK, at SK, and their ratio with its own information. We can confirm our understanding of the beam by comparing the neutrino spectrum measured by the near detector with that of the pion monitor prediction.

Principles to measure angle and momentum of pions

1. Optics (Pie shaped spherical mirror and photon detectors)

   A spherical mirror is used to measure angle and momentum of pions. It has interesting properties; Cherenkov photons are focused on same ring at the focal plane if they are emitted by particles which have the same beta and angle. (Fig. 4.15) This focusing effect is independent of the particles' positions. This allows us to measure the angle and beta of the pions.



Figure 4.15: A principle of the spherical mirror

Furthermore we designed the spherical mirror to be pie-shaped like Fig. 4.16



Figure 4.16: The spherical mirror of the pion monitor.

Initially, we planned to use a round mirror, however the reflected image is distorted if the round mirror has a kick angle. For example, Fig. 4.17 shows MC simulation results of this distortion in kick angle of 30 and 45 degree cases. These images are the Cherenkov photon distribution at the focal plane. The particles were assumed to have β=1 with the same angle around the mirror. The round mirror is 70 cm in diameter, and 4000 mm in radius of curvature. The Cherenkov radiator thickness and refractive index is assumed to be 30cm and n=1.0027, respectively. In this case, the radius of Cherenkov ring at the spherical mirror is ~2mm. The ring image from one particle is contained by the spherical mirror.



Figure 4.17: The ring image of the Cherenkov light on the focal plane using a round mirror. Left figure: round mirror with kick angle 30 degree. Right: 45 degree.

We define the "kick angle" as the angle between the beam direction and the normal of the spherical mirror around the beam center (Fig. 4.18). In the previous figure (Fig. 4.17), the angle of all particles is parallel to the beam direction.



Figure 4.18: The definition of the kick angle of a spherical mirror

Our mirror must have a large kick angle because the photon detector at the focal plane has to avoid the primary beam. On the other hand, pie-shaped mirror does not create any distortion, as shown in Fig 4.19.

Moreover a pie-shape has an advantage of detecting only the radial divergence of the pions. Radial and azimuthal divergence to the beam are defined like Fig. 4.20. Pions have much larger radial divergence than azimuthal divergence. Thus a pie-shape is suitable for detecting the pion divergence. Since a round mirror is sensitive to all directions of the pion divergence, it is difficult to separate radial and azimuthal contribution.

We have to assume azimuthal symmetry of the π beam in using this shape since we are observing only 1/30 of the total beam. The systematic errors caused by this will be discussed later.

2. Photon detector

A photon detector is installed on the focal plane like Fig. 4.21. One dimensional detector design has enough power to analyze the pions' kinematics. If we use a spherical mirror like Fig. 4.16,



Figure 4.19: The ring image of the Cherenkov light on the focal plane using a pie-shaped mirror. The kick angle is 30 degrees. The condition of the particles is the same as Fig. 4.17



Figure 4.20: Radial and azimuthal divergence.

the Cherenkov ring image at the focal plane can move along vertical axis. MC simulation proves that the ring image moves predominantly along the vertical axis (Fig. 7.1).



Figure 4.21: Position of the photon detectors with respect to the ring images

Principle to measure momentum of pions

1. Variable gas pressure

   It is essential to take data at various gas pressures for the measurement of the momentum of the pions. The Cherenkov threshold for a pion of given momentum varies with the gas pressure.

   Seven variable gas pressures are set for the pion momentum measurements. Those are summarized in Table 4.1

Pressure (atm)	Refractive index	Pion Cherenkov Threshold (GeV/c)
0.34	1.00047	4.6
0.42	1.00058	4.1
0.53	1.00074	3.6
0.68	1.000945	3.2
0.92	1.00128	2.8
1.24	1.00170	2.4
1.70	1.00236	2.0

Table 4.1: Gas Pressure set in the pion monitor run

Since we have to avoid severe primary proton beam background, the refractive index should be lower than n=1.00264 which corresponds to Cherenkov threshold of 12 GeV kinetic energy of proton. This limit the sensitivity for the pion momentum to be higher than $\sim$2 GeV/c. Figs. 4.22 and 4.23 show the result of MC simulation for the momentum and beta distribution at the pion monitor location, respectively.

There are lots of electrons and positrons in the beam. The way to handle these backgrounds against pion signals will be discussed in chapter 7.

4.2.2 Hardware Set up of Pion Monitor

As shown in Fig. 4.24, the pion monitor is situated between the 2nd horn and the decay pipe. The right side of this figure is upstream of the beam. The pion monitor is designed to be retractable. It is moved to the beam-line only when we make a pion monitor run. Otherwise it is hidden at the escape position to protect it from radiation and not to disturb the beam.

The apparatus of pion monitor is designed based on the above principles. Technical points to be considered in designing it are as follows.



Figure 4.22: The momentum distribution of four kind of particles/10^5protons after the 2nd horn. (protons, pions, muons and electrons)



Figure 4.23: The beta(v/c) of various particles. Top left figure shows the beta of pions, top right is e^+e^-, bottom left is protons bottom right is muons.



Figure 4.24: The 2nd horn, the pion monitor and the entrance of the decay pipe in the T-station

1. Radiation hardness. : The pion monitor is located in the primary beam-line. This causes severe radiation level.
2. Pulse response to intense photons.: The photon detector receives a lot of photons within 1μs. $1.0\times10^9/\mathrm{cm}^2$ level of photons comes to the photon detector.
3. Mechanical strength for gas pressure.: The gas vessel of the pion monitor has both inside and outside pressure because variable gas pressures are needed. We made a mechanical test for the window of the pion monitor using water, which is discussed later.
4. Large acceptance for the pion beam.: The pion beam is very broad after the 2nd horn (Fig. 4.25: radial distributions of pions).
5. Minimum material to the beam-line : This is not only for the small background creation (interaction between material and particles), but also for small heating up.
6. Remote control and monitoring system.: There is strong level of radiation around the pion monitor during and even after the beam-time. This requires a stable and remotely controllable system to handle various functions.

Designed pion monitor is shown in Fig. 4.26. The photograph of the gas vessel with the moving system of the pion monitor is shown in Fig. 4.27.



Figure 4.25: Radial distribution of pions after the 2nd horn (MC)

R&D was performed on the following items with serious care. We will explain these items in order.

1. Gas selection
2. Gas system
3. Spherical mirror
4. Photon detector
5. Gas vessel

6. Calibration system

7. Readout system



Figure 4.26: Pion monitor

Selection of gas

We want to measure the pion momentum as low as possible since it is important to know the low energy neutrino flux to investigate a lower Δm^2 region. This means that the refractive index should be as high as 1.00264, which corresponds to the Cherenkov threshold for 12 GeV kinetic energy protons.

Freon gas is the best solution to get such a high refractive index. It is good also from the safety point of view because it is not flammable or poisonous.

Refractive indices of various gases were studied. An interferometer was used to measure them as shown in Fig. 4.28.

The beam size of the He-Ne laser light is enlarged by the laser beam expander. It goes to the vacuum vessel which is separated into two regions inside. One part of it is kept at vacuum ($\sim$ 1 torr) and the other side is being filled with gas with a constant rate. In this system, interference stripes in the microscope move proportionally to the gas pressure. The number of stripes which pass through the one fixed point in the microscope area are counted as shown in Fig. 4.29. This number is related to the refractive index n by the following formula;

$$N = \frac{n-1}{\lambda_0/d}, \tag{4.1}$$



Figure 4.27: The photograph of the gas vessel with the moving system of the pion monitor



Figure 4.28: Interferometer

where, λ_0 is wavelength of laser (632.8 nm), d is length of the vacuum vessel (230.0 mm). In the example of Fig. 4.29, N=3 under $\Delta P=P_1-P_0$, thus the change in the refractive index is $(n-1)=8.254\times10^{-6}$.



Figure 4.29: The interference stripes in the microscope.

It was concluded that R-C318 freon gas has the highest refractive index (n=1.00123, at 25°C, 1 atm. : Fig. 4.30)*

Gas system

A remotely controllable gas system is prepared to vary the freon gas pressure in the gas vessel.(Fig 4.31) It is a closed system, consisting of a gas supply system, a gas recirculation system and an interferometer calibration system.

The gas supply system consists of gas bottles, 100 meter long pipe with 1″ diameter to connect the highly irradiated target station to safe outside world, a lot of valves, gauges and so on. The 100 meter pipe has a heating system so as not to liquefy the gas.† To control the pressure below the 1 atm inside the gas vessel of the pion monitor, we have a rotary pump system nearby the pion monitor.

The gas recirculation system has a pump and a gas buffer. This system is designed to reuse the gas that is once filled in the gas vessel.

The interferometer calibration system is quite similar to the system in Fig. 4.28. It aims to measure the air contamination of the gas in this closed system. The contamination leads to lower indices of refraction than expected. Correction is needed for the refractive index if the contamination is found.

Air-tightness of the gas vessel of the pion monitor is tested employing the vacuum. The gas vessel kept the vacuum within 20 hours from 1.3×10^{-1} torr to 3.2×10^{-1} torr. This is stable enough, taking into account the refractive index of the freon gas.

Spherical mirror

The spherical mirror was made by Kokusai-Shouji K.K. The radius of curvature of the mirror is 6000 mm and the size is 600 mm×150 mm. It is made of Pyrex glass which is partially coated with Al and frosted by sand to make a pie-shape (Fig. 4.32). A hardness for the radiation and heating-up was

* The refractive index of this gas has a wavelength dependence. It is described in chapter 7. These values are for wavelength of 632.8 nm

† C_4F_8 has low vapor pressure. The vapor pressure is about 2.3 atm at a temperature of 20 degrees.



Figure 4.30: The result of the refractive index measurement

tested with intense proton beam before the K2K experiment. The quality of the optics was tested using an LED.

1. Test of radiation and heating-up hardness by a beam
   The test of heating up and radiation hardness to the beam was done at the KEK booster beam dump. The intensity of the KEK booster beam at this test was about 1.2×10^{12} ppp; the repetition rate was about 20 Hz; kinetic energy of the protons was 500 MeV; and the RMS width of the fitted one dimensional profile (using a Gaussian) is $\sim$1 cm, while in the real K2K beam case, the intensity is 6.0×10^{12} ppp and the repetition rate is 1 pulse/2.2 sec. These parameters are summarized in table. 4.2

	K2K	Booster beam-dump
Beam intensity	6.0×10^{12}ppp	1.2×10^{12}ppp
Beam width	1μs	50ns
Repetition	1pulse/2.2sec	72pulse/4sec
Kinetic energy	12GeV	500MeV

Table 4.2: Comparison of proton beam parameters between the K2K experiment and the KEK Booster beam-dump

   This test beam is much more severe than the real one regarding heating up since the cooling time is 40 times shorter and dE/dX is as large as twice.

   The glass was exposed to a total of 6.3×10^{16} protons in this test. This corresponds to about 6 hours radiation of the real K2K beam. 4 cm $\times$ 4 cm $\times$ 6 mm(thickness) Pyrex glass stood under this severe situation. The Al coating part was not clouded by this radiation level, although this was checked only by eye, not quantitatively. It was concluded that the Al coated Pyrex glass mirror was strong enough to be used in the real experiment.

2. Test of optics quality using LED
   The optical quality of this spherical mirror was tested using an LED (Fig. 4.33).



Figure 4.31: The gas system of the pion monitor



Figure 4.32: The pie-shaped spherical mirror

Figure 4.33: LED test of the spherical mirror

Spherical mirrors focus light emitted from a point source at the center of the sphere on the point source itself (Fig. 4.34). We can measure the radius of curvature and check the imperfection of the mirror by illuminating the mirror with a point source, an LED. By moving a camera to find the most focused image of the LED, we measured the radius of curvature to be 5827 mm. We also measured the level of aberration to be negligible.



Figure 4.34: The characteristics of spherical mirrors. Spherical mirrors focus light emitted from a point source at the center of the sphere to the point source itself.

Photon detectors

Twenty modified R5600-01Q type PMTs (made by HAMAMATSU Photonics Corporation) are used for the photon detector.(Fig. 4.35)

These PMTs have 3 main different characteristics from standard ones(R5600-01).

1. Quartz window
2. Multi-Alkali(Sb-Na-K-Cs) photo-cathode material
3. Low gain

The reasons are following.

1. Quartz window

   This is for radiation hardness. It is well known that the standard window (BK7) gets dark under severe radiation while quartz is quite strong for radiation.

   In order to check it, radiation damage to a PMT window was tested at the K3 beam-line of KEK-PS. (Fig. 4.36)

   At first, we estimated total number of particles/cm^2 around PMT region for K3-line and K2K using a MC simulation. It is summarized in Table 4.3. ‡ This calculation shows K3 radiation has the same order of magnitude as the real experiment. This calculation has a large safety factor because the pion monitor is located far away from the beam-line except for pion monitor measurements.

   For a quantitative study of radiation damage, transparency ratios of BK7 and quartz were measured before and after this irradiation using a transmeter(Fig. 4.37).

‡ The span of K2K here is assumed to be full span. (10^{20}POT).